High range latch

134U Plus Series



CERTIFIED ACCORDING UNE-EN 12209:2004

Features


» Mortise lock for wooden doors.
» Distance between shafts: 70 mm.
» Backset: 50/60.
» Valid for both passage and deadbolt doors.
» Automatic unblocking of deadbolt: if the deadbolt is activated with an open door, this will be released when it is closed.
» Reversible latch made of AISI 304 wrought stainless steel. Silent, fire-resistant.
» Handle follower rod: 8mm. Deadbolt follower rod: 6 mm.
» 23 mm front, square or round-shaped.
» Housings conform to DN standard for double rapiers.
» Packaging in one single box.
» Certified according to the 12209 CE-EN standard.
» With strike protector.


Finishes

» Brass steel (HL)
» Nickel brass (HN)
» Glazed steel (AE)
» AISI 430 stainless steel (AI)
» Antique brass (LA)

Classification

3	S	8	1	F	0	N	A	B	0		
Category of use	Durability and load on latch bolt	Door mass and closing force.	Suitability for use on fire/ smoke doors.	Safety	Corrosion resistance and temperature.	Security and drill resistance.	Fields of application for doors.	Type of key manoeuvre and blocking.	Type of manoeuvre in t he follower rod	Requirements for key identification.	





Model	Backset. 1/2 round forend or square	Finish	Packaging
134UP	5R / 50	AE	1
134UP	5R / 50	HN	1
134UP	5R / 50	HL	1
134UP	5R / 50	AI	1
134UP	5R / 60	AE	1
134UP	5R / 60	HN	1
134UP	5R / 60	HL	1
134UP	5R / 60	AI	1